# RR-UB-500





## **Technical Specifications**

## **Areas of Applications**

- Gross weight: 45KG
- Power Supply: AC85v 264 v
- Working temperature:-20℃--+50℃
- Working Frequency :4KHZ—8KHZ
- Standard External size: 2230mm(H)X860mm(W)X480mm(D)
- Standard Internal size: 1990mm(H)X700mm(W)X400mm(D)
- Package size for door panels: 2290\*560\*190mm \*1ctn
- Package size for control unit: 760\*350\*260 mm\*1ctn









Port

Hotel

**Airport** 









Factory

tory Government

Bank



# Usage condition RR-UB-500

#### **Pinpoint Zone Detection**

The Uniqscan's exclusive multiple target pinpointing with 6 zones standard shows precise target location on the left, center and right side of the body from head to toe.

#### Program

When the program is self-diagnostic, it does not require initial or periodic calibration, modularization design, easy for maintenance and replacement.

#### Installation

RR-UB-500 design only 2 cables and 8 screws, operation instructions are simple. High density refractories are used to make the product stronger.

.....

### PRODUCT DETAILS

















- A. 5 Digital LED Count : Easy show & count passengers
- B. 8 Screws: Easy assembly and install;
- C. Socket: Easy connect both door panels;
- D. Power Line : Support UK / European / USA standard;
- E. Integrated Circuit Board: Intelligent circuit;
- F. Infrared Sensor : Accuracy check;
- G. Tamper Indication: Easy distinguish interference;
- H. Foot Cover: Easy fastness;



The RR-UB-500 Access Control Panel is designed for use by authorized personnel with specific, multi-level security with password protection, only the authorized person can operate; Sound & LED alarm: Both Side LED indicator, easily show where the metal is, Automatically count passengers and alarm times.

## PRODUCT PACKAGING



